
EWM-W173H

Advantech 802.11ax + BT 5.0 2T2R (HMC)



Features

- IEEE 802.11 ax/ac/a/b/g/n (2.4GHz+5GHz) standard
- Half-Size Mini PCIe Card interface
- 2T2R (Support WiFi/BT co-existence)
- Operating temperature: -40 ~ 85 °C
- Supports Linux and Android

C E FCC ROHS

Specifications

Main Chipset	Broadcom AP6275P	
Tx/Rx	2TX/ 2RX	
Standard Conformance	IEEE 802.11ax + BT5.0	
Form Factor	Half-Size Mini PCle Card	
Interface	Wi-Fi: PCle BT:USB	
Operation Voltage	DC 3.3V	
Power Consumption	TX Mode: 937mA (Max.) RX Mode: 94mA (Max.)	
Security	64/128-bits WEP, WPA, WPA3, 802.1X	
OS Supported	Linux / Android	
Temperature Ranges	Operation: -40 ~ 85 °C	
Dimensions (L x W x H)	29.85 x 26.65 x 2.5 mm	

Ordering Information

Part No.	Product Description	
EWM-W173H01E	AP6275P, IEEE 802.11ax +BT 5.0, 2T2R, HMC, WiFi interface: PCIe, BT interface: USB	

Suggested Antenna and Cable

- 1	Wodel	Part No.	Specifications
,	AIW-512	1751000651-01	Omni-directional radiation pattern, compatible for WiFi5/6/6E/7
,	AIW-513	1751000717-01	Omni-directional radiation pattern, compatible for WiFi5/6/6E/7, IP67 level
		1751000647-01	WiFi Coaxial Cable, 10cm, RP-SMA female to IPEX1
		1751000627-01	WiFi Coaxial Cable, 15cm, RP-SMA female to IPEX1
		1751000634-01	WiFi Coaxial Cable, 20cm, RP-SMA female to IPEX1
		1751000626-01	WiFi Coaxial Cable, 25cm, RP-SMA female to IPEX1
		1751000588-01	WiFi Coaxial Cable, 30cm, RP-SMA female to IPEX1